



Architectural & Design Guidelines

Stage 2 RPL

Includes:

Lots 1 to 17, Block 86

Lots 1 to 9, Block 88

February 2005

CONTENTS:

Section	Description
1.0	OBJECTIVE
2.0	ARCHITECTURAL THEME
3.0	STREETSCAPE
4.0	HOUSE SIZE
5.0	SITE PLANNING AND GRADING
6.0	GARAGE/DRIVEWAY
7.0	IDENTICAL ELEVATION
8.0	EXTERIOR COLORS
9.0	CORNER LOTS
10.0	ROOFING
11.0	EXTERIOR FINISHES
12.0	FENCING
12.1	Landscaping
12.2	Accessory Buildings
13.0	INTERPRETATIONS
14.0	SITING
15.0	Consultant
15.1	City Regulations
15.2	Grading
15.3	Plot Plans
16.0	SUBDIVISION APPEARANCE
16.1	Signage
16.2	Excavation Material
16.3	Clean Up
16.4	Construction Activity
17.0	APPROVAL PROCESS
18.0	DAMAGE DEPOSITS
18.1	Deposit Return Procedure

DIRECTORY:

Developer	MLC Group Inc.	420-0044 (Fax 423-0044)	Dave McDougall Arlene Zingle	1000, 10104 103 Ave. Edmonton, AB. T5J OH8
Engineers	Stantec Consulting	917-7000 (Fax 917-7289)	Tom Baba	10160 - 112 Street Edmonton, AB. T5K 2L6
Architectural Applications	Mariah Consulting	437-3443 (Fax 436-5920)	Laurie Lebirk	#208, 5807 - 104 Street Edmonton, AB. T6H 2K4
Surveyor	Stantec Geomatics	917-7000 (Fax 917-7289)	Brent Rudko	10160 - 112 Street Edmonton, AB. T5K 2L6
Solicitor	Oshry & Company	428-1731 (Fax 420-6290)	Karen Oshry	1004, 10104 - 103 Ave. Edmonton, AB. T5J OH8
Geotechnical Consultants	J.R. Paine & Assoc.	489-0700 (Fax 489-0800)	Rick Evans	3051 Parsons Road Edmonton, AB. T6N 1C8

1.0 OBJECTIVE

The objective of these architectural guidelines is to ensure the very highest standard of visual

appeal and image; ensuring compatibility among homes and integration of the community into the natural landscape. Outlining the opportunities and constraints of building, these guidelines will assist builders, designers and home buyers in achieving problem free construction.

2.0 ARCHITECTURAL THEME

The natural landscape and history of the valley provides the perfect setting for this collection of Traditional homes.

Appropriate house styles will incorporate the elements and characteristics of the traditional designs of Craftsman, Georgian, Queen Anne and National.

Building forms, roof lines, entrance treatments and detailing will reinforce the style.

The comforts of things familiar and the simplicity of times long past, this will be the character of South Terwillegar.

3.0 STREETSCAPE

Relative massing, siting and style will ensure each home compliments the streetscape and adjacent homes. Two story models only, will be permitted in this stage of South Terwillegar.

Entranceways will be covered at the first level. The style, width, height and detailing of entranceways will together create a sense of arrival.

Building massing, siting and style may be adjusted and/or alternate treatments requested to reinforce the streetscape.

4.0 HOUSE SIZE

Houses are to have a consistency of mass and volume within the streetscape. The minimum house width is 20' on all lots.

5.0 SITE PLANNING AND GRADING

Site planning and grading must accommodate the natural slope of the land with variations in grade absorbed within the building mass as much as possible. Lot grading must be in strict conformance with the approved grading plan for the subdivision.

Special attention is to be given the treatment of exposed concrete foundation walls. A maximum of 2' of parged concrete will be permitted on all elevations of the homes. Variation in grade and basement design may require cladding material be lowered or extended to within 2' of ground level.

Front entry steps are to be a maximum of four risers per set. Where the grade calls for more than four risers, the run must be split. Exceptions to this requirement may be granted in consideration of unique design or topography.

Homes will be reviewed on their individual merits of design, massing, proportion and compatibility and, where the Architectural Consultant considers the plan to be exceptional, and, provided that

the house conforms with the general trend of the neighborhood, exceptions may be considered.

6.0 GARAGE/DRIVEWAY

The front walkway must be a minimum of poured concrete in broom finish. Individual patio blocks will not be permitted.

A 20 x 20 poured concrete parking pad must be provided concurrent with house construction. The approach to the lane may be paved with asphalt or concrete.

Detached garages should be consistent in style, finish and color with the design of the house.

7.0 IDENTICAL ELEVATIONS

Similar or approximately identical elevations must not be repeated with two lots (X0AX). A minimum of three different models, each with two distinctly different elevations will be provided. When the same model with alternate elevations are sited side by side, the rear elevation must also be addressed for repetition.

Repetitive use of elevations will be monitored to ensure interesting streetscapes.

8.0 EXTERIOR COLORS

Colors will be approved on an individual basis. Colors will not be duplicated on adjacent lots. The use of a third accent color is strongly encouraged. In keeping with the character of the neighborhood and in consideration of blended streetscapes, pastel colors are not permitted. Darker color palettes will dominate the streetscapes. White and lighter cladding colors may be used moderately in combination with darker palettes in contrast.

9.0 CORNER LOTS

Houses on corner lots require special design consideration. Flanking side elevation will have suitable front elevation treatment with principal roof planes sloping toward view. Corner elevations require variation in wall planes, substantial roof line between floors, appropriate wall heights, window placement and detailing.

10.0 ROOFING

Roof slopes and overhangs will be consistent with the architectural style of the home.

The roofing materials/colors may be selected from the following:

- IKO, Cambridge Series 30, in Weatherwood or Dual Black
- BP, Harmony Series 30, in Stonewood or Shadow Black
- GAF, Timberline 30, in Weatheredwood or Charcoal Blend

Chimneys and flues must be contained within a corbeled chase, finished in a style consistent with the home design.

11.0 EXTERIOR FINISHES

To achieve the standard and caliber of visual appeal, a requirement for architectural detailing and continuity will apply to all homes.

Detailing will be consistent with the architectural styling of the home. Stone or brick, a minimum of seventy- five square feet will be required at the front elevation. If column bases are masonry, they must extend to grade.

An emphasis on entrance treatments is a requirement. Such treatment may include verandas and covered porches, a minimum of 5' deep. Wooden verandas and porches must be finished to grade.

The use of window and door surrounds will be a feature on all homes. Trim will be a minimum 6" .

The application of siding only, is permitted in Stage 2.

All trim details and masonry must be returned 18" around corners.

Homes will be reviewed on their individual merits of design, massing proportion and compatibility and, where the Architectural Consultant considers the plan to be exceptional, and, provided that the house conforms with the general trend of the neighborhood, exceptions may be considered.

12.0 FENCING

Wood fencing shall be consistent in design and color with the fencing style established for the community, an illustration of which is attached.

13.1 Landscaping

It is the responsibility of the homeowner to landscape the front yard. In the case of corner lots, the front yard shall include the flanking side yard to the sidewalk, curb or boulevard and to the rear corner of the house.

The minimum landscape standard for all lots shall consist of sod, one tree and a prepared shrub bed containing at least six shrubs. The minimum deciduous tree shall be 2" caliper, measured 6" above ground. The minimum coniferous tree (spruce or pine) must be a minimum 6' tall. Shrubs shall be 2' in height or spread. A prepared bed is defined by edging (landscaping vinyl, brick, concrete, etc.)

All landscaping must be completed, in accordance with the requirements, within six months of completion of the house (subject to seasonal limitations). To ensure compliance with the landscaping requirements, a \$1,000.00 security deposit must be paid by the Purchaser, to be refunded by the Builder, upon confirmation of the satisfactory completion of the landscaping.

13.2 Accessory Buildings

The side wall elevations of all ancillary buildings and garden sheds shall not extend higher than adjacent fencing. Where visible from a public adjacency (i.e. all perimeter lots and corner lots), accessory buildings must be consistent in style, finish and color, with the house. Roof style and materials are to match the materials used on the roof of the house.

13.0 INTERPRETATION

The enforcement, administration and interpretation of these guidelines shall be at the discretion of

MLC Group Inc. or it's designated consultant. The unfettered application of these guidelines shall be without notice or precedent.

15.0 SITING

15.1 Consultant

Check with the Architectural Consultant for all applicable drawings, and any special conditions.

15.2 City Regulations

Ensure that city regulations are met and note relevant plans regarding utilities and rights of way.

15.3 Grading

Check Building Grade Plans and conform to them. Do not grade to existing vacant lots or unfinished lanes, but to elevations provided.

15.4 Plot Plans

Plot plans and stakeout must be carried out by the designated surveyor only. Plot plans must include the following:

- * Scale 1:300 metric.
- * North arrow.
- * Municipal address.
- * Legal description of property.
- * All property lines, designated and dimensioned.
- * Size and location of proposed building(s) dimensioned to property lines, existing building and other structure where applicable.
- * All cantilevers (including floor, bay windows, fireplaces, eaves, etc.).
- * Abutting streets, avenues, reserves, etc. Easements and utility right-of-way labeled and dimensioned, accurately figured, explicit and complete.
- * Spot elevations around building and drainage directions.
- * Dimensions from property line to sidewalk and face of curbs.

16.0 SUBDIVISION APPEARANCE

16.1 Signage

In order to maintain cohesiveness for signage within the subdivision, all signage will be supplied by the Developer, i.e. all model signs, directional signs and general information signs. The only signage to be supplied by the Builders Group will be on lots owned or sold by that Builder. Excessive abuse of signage, including sandwich boards may necessitate removal of ALL Builder's and Realtor's signs.

16.2 Excavation Material

All Builders must ensure that all excavation is kept within the confines of their lot. Any spillage on a road, land, sidewalk or neighboring lot must be removed immediately or the Developer will arrange for its removal and invoice for expenses.

16.3 Clean Up

Builders should encourage timely removal by all subtrades of litter on building sites. Failure to comply will result in a clean-up bill being charged to the lot. Supply of bins by the Builder is recommended. Any general clean-up of the subdivision implemented by the Developer can and will be charged pro-rata to all builders.

16.4 Construction Activity

Each Builder is responsible for inspecting the condition of curbs, sidewalks, street lights, services, etc. on his lot and must submit written notice of any damages to the Developer prior to commencing construction, otherwise costs for repairing any damages becomes the sole responsibility of the Purchaser.

17.0 APPROVAL PROCESS

Prior to building the Builder inspects the lot and all services. All discrepancies or damage to be reported in writing with the application and copy forwarded to the Developer.

Before applying to the City for a development permit, the applicant shall submit plans for approval of MARIAH CONSULTING LTD. Application shall include the following:

- a) One complete set of house plans; ¼" or 3/16" to 1; scale
- b) Two Copies of the Plot plan, prepared by Stantec Geomatics, 1:300 scale
- c) Completed application form.
- d) Material and color samples, as required.

MARIAH CONSULTING LTD. will review the plan and recommend approval, modification, or rejection of the application based on the adherence of the plans to these guidelines. Should disputes arise, the Developer shall make the final decision on the acceptability of plans. Once approved, MARIAH CONSULTING LTD. will send a copy of the application indicating any changes to the applicant. After approval, the plans may not be altered without prior approval of MARIAH CONSULTING LTD. MARIAH CONSULTING LTD. will keep an up-to-date record of plans showing house types, color, roof lines and grades, to advise the applicants of how their proposed house will best fit into the existing situation.

Approval of any and all house plans will be at the sole and unfettered discretion of the Vendor.

No stake-out will be granted until approved by MARIAH CONSULTING LTD.

18.0 DAMAGE DEPOSIT

A damage deposit of Letter of Credit in the amount of \$5,000.00 (regardless of the number of lots) is due prior to house plan and grade approval to cover:

1. Contravention of architectural objectives.

2. Possible damage to:

- (a) Curb stop - water valve
- (b) Sidewalks, curbs and gutters
- (c) Driveway aprons and asphalt
- (d) Boulevard landscaping and trees
- (e) Rear gutters and walkways
- (f) Light standards
- (g) Fire hydrants
- (h) Cathodic Protection points
- (i) Grading and drainage swales
- (j) Fencing

18.1 Deposit Return Procedure

1. Exterior completed in accordance with these guidelines and as approved by the architectural consultant.
2. Landscaping satisfactorily completed as per requirements.
3. Rough grading certificate & city approval of same, from the City of Edmonton Drainage Branch.
4. Water valve exposed and marked.
5. Sidewalks, street, lane, gutters and curbs cleaned.
6. Application made in writing to MARIAH CONSULTING LTD (form attached).

Upon completion of construction, site works and landscaping, a final inspection is done to ensure compliance with the architectural guidelines and to check for any damages to municipal improvements. The following items must be completed prior to a request for final inspection:

- Home constructed in compliance with the Guidelines and the approved plan
- Construction complete including seasonal work on exterior, site cleared of all debris, sidewalks and curbs cleaned, cc marked and exposed
- Landscaping completed in accordance with guideline requirements
- Grading certificate for rough grade is provided with City approval

To initiate the final inspection, a request form accompanied by the approved grading certificate must be forwarded by the builder to Mariah Consulting Limited.